



**Gitterrost MT 33,3 x 33,3 - Material: St 37 - Tragstab laut Tabelle**

Stützweite [mm]		200	300	400	500	600	700	800	900	1000	1100	1200	1300	1400	1500	1600	1700	1800	1900	2000
Klasse	<b>PKW</b>	30x4	30x4	30x5	35x4	35x5	40/5	45/5	45/5	50/5	60/4	60/5	60/5	60/5	70/4	70/5	80/4	80/5	90/4	90/5
Raddruck	5,0 kN			35x4	40x4	40x4	45/4	50/4	50/5	60/4		70/4	70/4	70/4		80/4		90/4		
Lastwürfel	200x200mm																			
Klasse	<b>Klein LKW</b>	30x4	30x4	30x5	35x5	40/5	45/5	50/5	50/5	60/4	60/5	60/5	70/4	70/5	70/5	80/4	80/5	90/4	90/5	100/5
Raddruck	7,5 kN			35x4	40x4	45/4	50/4	60/4	60/4		70/4	70/4		80/4	80/4		90/4			
Lastwürfel	200x200mm																			
Klasse	<b>LKW 6 t</b>	30x4	40x5	45x5	60x4	60/5	70/5	80/4	80/5	90/5	90/5	90/5	100/5	100/5	110/5	110/5	110/5	120/5	120/5	120/5
Raddruck	20,0 kN		45x4	50x5		70/4	80/4		90/4											
Lastwürfel	200x200mm																			
Klasse	<b>LKW 12 t</b>	30x4	45x5	60x5	80x4	90/5	90/5	100/5	110/5	120/5	120/5	130/5	140/5	140/5	150/5	150/5				
Raddruck	40,0 kN		50x5	70x4																
Lastwürfel	200x300mm																			
Klasse	<b>LKW 30 t</b>		45x5	60x5	80x5	90/5	100/5	110/5	120/5	130/5	130/5	140/5	150/5	150/5						
Raddruck	50,0 kN		50x4	70x4	90x4															
Lastwürfel	200x400mm																			
Klasse	<b>LKW 45 t</b>		40x4	70x5	90x5	100/5	120/5	130/5	140/5	150/5										
Raddruck	75,0 kN			80x4																
Lastwürfel	200x500mm																			
Klasse	<b>LKW 60 t</b>			60x5	90x5	110/5	130/5	140/5	150/5											
Raddruck	100,0 kN			70x4																
Lastwürfel	200x600mm																			

Bremsfaktor 1,4 berücksichtigt | Die angegebenen Werte stellen die max. Tragfähigkeit der Roste dar | Stützweite = lichte Weite zwischen den Auflagern